

DFTG40

TGR60



Technical features

Series DFTG40

• Container	metal
• Power supply voltage	230 V 50/60 Hz 140 W
• Protection	external by rapid fuse, internal by electronic self-resetting fuse
• ON/OFF switch	rear
• Maximum voltage on cutting wire	9 VAC
• Front plate	for setting and visualising load with LED display
• Dimensions	155 mm x 235 mm x 130 mm
• Weight	4,8 kg
• Cutting blade width	70 mm

Series TGR60

• Power supply voltage	230 V 50/60 HZ
• Power output	60 W
• Ignition time	6 sec.
• Weight	1 kg
• Cutting blade width	29 mm

General features

Series TGR60 and DFTG40 devices for hot cutting expandable braided polyester sleeving are particularly suitable for use on production lines and as the TGR60 is portable and the DFTG40 is the table version, they meet any type of need.

**DEVICE FOR HOT
CUTTING EXPANDABLE
BRAIDED POLYESTER
SLEEVEING**

**"SERIES TGR60"
"SERIES DFTG40"**

**COMPANY WITH QUALITY MANAGEMENT
SYSTEM CERTIFIED BY DNV
= ISO 9001:2008 =**

La RTE si riserva il diritto di apportare eventuali modifiche al presente catalogo senza preavviso. *RTE reserves the right to make any modification to this catalogue without prior notice.*
I dati contenuti in questo catalogo sono basati su test che riteniamo validi, ma che non costituiscono garanzia implicita od espressa. Potranno variare in qualunque momento in funzione di nuove conoscenze od esigenze, senza preavviso da parte della ns. società.

The information given in this catalogue is based on tests we believe to be valid, but it does not constitute intended or explicit guarantee. The information may vary at any time in accordance with updated knowledge and needs, without prior notification from our company.

Consigliamo ai ns. clienti di valutare l' idoneità dei ns. prodotti secondo la loro applicazione specifica.
We recommend that our customers assess the suitability of our products in regard to their specific application.

In nessun caso ci riterremo responsabili per qualsiasi eventuale danno, indiretto o conseguente alla vendita, rivendita, trasferimento, uso o uso improprio del prodotto.
In no case shall we be considered liable for any damages, whether indirect or in consequence of the sale, resale, transfer, use or incorrect use of the product..



DIREZIONE COMMERCIALE

Via Borgo Roldi, 49 - 26025 PANDINO (CR) - ITALY

Tel. 0373 920659 - 0373 920660 - Fax 0373 90422

e-mail: info@rtecomponenti.it - www.rtecomponenti.it - www.rtecomponents.com