

HL



Technical features

Series HL1920E

• Power supply voltage	230/240 V 50 HZ
• Power output	2000 W
• Temperature	80÷600 °C
• Temperature regulation	with knob
• Volume of air	switch pos. 1): 150 LT/MIN. switch pos. 2): 300 LT/MIN. switch pos. 3): 500 LT/MIN.
• Dimensions (length x width x height)	253 mm x 84,5 mm x 200 mm
• Weight	850 g

Series HL2020E

• Power supply voltage	230/240 V 50 HZ
• Power output	2200 W
• Temperature	switch pos. 1): 80 °C switch pos. 2-3): 80÷600 °C
• Temperature regulation	in 10 °C steps
• Temperature visualisation	liquid crystal display
• Volume of air	switch pos. 1): 150 LT/MIN. switch pos. 2): 300 LT/MIN. switch pos. 3): 500 LT/MIN.
• Dimensions (length x width x height)	253 mm x 85,5 mm x 200 mm
• Weight	860 g

**HEATGUN FOR
SHRINKING
HEATSHRINKABLE
TUBING**

"SERIES HL"

General features

Series HL heat guns for shrinking heatshrinkable tubing, light and easy to handle, are particularly suitable for use on production lines. They are also available in the HL2020E electronic version, in which the output temperature of the hot air is constantly visualised.

**COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =**

La **RTE** si riserva il diritto di apportare eventuali modifiche al presente catalogo senza preavviso. *RTE reserves the right to make any modification to this catalogue without prior notice.*
I dati contenuti in questo catalogo sono basati su test che riteniamo validi, ma che non costituiscono garanzia implicita od espressa. Potranno variare in qualunque momento in funzione di nuove conoscenze od esigenze, senza preavviso da parte della ns. società.

The information given in this catalogue is based on tests we believe to be valid, but it does not constitute intended or explicit guarantee. The information may vary at any time in accordance with updated knowledge and needs, without prior notification from our company.

Consigliamo ai ns. clienti di valutare l'idoneità dei ns. prodotti secondo la loro applicazione specifica.
We recommend that our customers assess the suitability of our products in regard to their specific application.

In nessun caso ci riterremo responsabili per qualsiasi eventuale danno, indiretto o conseguente alla vendita, rivendita, trasferimento, uso o uso improprio del prodotto.
In no case shall we be considered liable for any damages, whether indirect or in consequence of the sale, resale, transfer, use or incorrect use of the product..



DIREZIONE COMMERCIALE

Via Borgo Roldi, 49 - 26025 PANDINO (CR) - ITALY

Tel. 0373 920659 - 0373 920660 - Fax 0373 90422

e-mail: info@rtecomponenti.it - www.rtecomponenti.it - www.rtecomponenti.com